

the future is now - be there with us™

Infra-Red & Radio
Remote Control
Crane Systems

COMMANDER™
COMMANDER

Horizontal & Vertical
Collision Avoidance
Crane Systems

Sales Specification for Crane Remote Control System **€3™ Joy Stick Radio Transmitter with RD-17™ Teachme™ Receiver Decoder**



The **COMMANDER™ Teachme™** dual channel (CAT 3) dual microprocessor controlled digital **Radio** remote control system with **€3™** joy stick transmitter is a **FAST, POWERFUL & FLEXIBLE** product. Specially designed for the safe and cost effective operation of 3, 4 or 5 motion (or more) electric overhead cranes and other electrically powered equipment requiring multi speed or variable speed joy stick remote control from a ground based operator. The **Teachme™** remote control system uses a receiver decoder that is sized to suit the application and to minimise interface redundancy. One standard **RD-17™** receiver decoder is expandable with additional relay interface PCB's, Analogue drivers for up to 4 motions and **TruTandem™** multiple crane control. The **RD-17™** receiver decoder can be reprogrammed at any time (during the **Teachme™** access time window) with a replacement transmitter.

COMMANDER™ €3™ joy stick transmitters have been designed for maximum flexibility for multiple configurations and feature advanced bi-directional 2 axis (X-Y) mechanisms with gated or free axis option, and with up to 5 stepped or step-less speed steps. Each Joy Stick lever has an inbuilt start up protection and dead man button for additional safety and spring return levers that are biased to the centre off position. The **€3™** joy stick transmitter can be supplied with combinations of auxiliary pushbuttons, rotary switches and supervisory key switch options available as standard feature options. Infra-Red safety **CloseStart™** option in built. Command legends included to suit the country of destination.

Specialist Designers & Manufacturers of Industrial **Infra-Red & Radio** Remote Control; **Infra-Red, Ultrasonic & Microwave** Crane Detection Systems for Horizontal & Vertical (multi-level) applications; Simplex & Duplex Data Communicators; High Integrity Control Systems, Eddy Current Brakes & Closed Loop Controllers for High Integrity Heavy Lift Cranes & other Material Handling Applications: **U.K. Designed & Manufactured.**

TP **TechPoint™**

Technical Details for **E3™ Joy Stick Radio Transmitter with RD-I7™ Teachme™ Receiver Decoder**



RD-I7™ Teachme™ Receiver Decoder

Safety	CAT 3, Two FG MCR's & dual channel μ P's (microprocessors)
Enclosure	Sheet Steel with hinged door
Size	338W x 250H x 97D (mm)
Finish	Powder coated in Black
Cable ports provided	Qty 1 @ 25mm, Qty 3 @ 20mm
AC Voltage Version	42V-230V AC (3 formats) (DC to order)
Environmental	-10°C to +55°C IP54
Volt Free Relays	17 - 33 N.O. volt free contacts (N.C. & Latch available)
Analogue drivers	Qty 4 Analogue drivers for inverters with stepped or step-less interface
Power & Interface	Plug & socket I/O terminal connectors
Signal Input	BNC co-axial from PLL Radio receiver module
MLC Monitoring	Voltage or optional current monitoring (subject to VFD/FVD's).
Diagnostics	Alphanumeric and LED's
Security Codes	Teachme™ coding from the transmitter
Expandable with	Up to Qty 2, 8 relay PCB's/Analogue) / TruTandem™

RFRxE™ PLL Radio Receiver (with RF cable)

Type (extruded frame)	Omni-directional (under-crane mount) anodised Blue
Operating Range	150+ Metres (free airspace)
Environmental	-10°C to +55°C IP55
Connection	Single BNC co-axial port

E3™ Joy Stick Radio Transmitter

Safety	CAT 3 EM Stop & dual channel μ P's (microprocessors)
Construction	Fabricated Aluminium (Hard Grade)
Dimensions	240W x 130H x 164D (mm)
Finish	Powder coated in Blue
Weight	2 kg (with battery)
Battery Type	Rechargeable NiMH pack
Environmental	-10°C to +55°C IP55
RF Frequency	433-434 MHz (Installer channel set) (other frequency options)
Primary Controls	Qty 2 bi-directional joy sticks
Speed Steps	Up to 5 or variable (step-less)
Auxiliary controls	Push buttons, rotary & key switches
Diagnostics	Battery warning & status LED's
Security Codes	Factory set
Operating Range	150+ Metres Approx (free airspace)
Safety Crane Start Up	Infra-Red safety CloseStart™ option in built to all radio systems
Charge Life	18 hours @ 100% duty

E3™ Transmitter Battery Chargers

Fast/trickle version	40 minutes approximately in fast mode/auto trickle
Trickle only version	Constant current trickle charge
Environmental	-10°C to +55°C IP54
Power	230V AC (115V AC option)



© Copyright 2015

Commander Controls Limited, 12 High Hazels Road, Cotgrave, Nottinghamshire, NG12 3GZ, U.K.
 Tel: +44 (0) 115-989-0100; Fax: +44 (0) 115-989-0200; www.commander.co.uk; sales@commander.co.uk
 Publication CCL/E3/RD17/Radio Remote Control System (Issue 01-06-2015)

